



<b>Housing Material</b>	Die-cast aluminium	<b>IK Protection Class</b>	IK10
<b>Housing Color</b>	Grey	<b>Life Time L70 / B50</b>	50000 h
<b>Material of Lens</b>	Polycarbonate - PC	<b>Life Time L80 / B10</b>	50000 h
<b>Surface Structure of Lens</b>	Clear	<b>Switching Cycles</b>	100000
<b>Protection Class</b>	Protection class I/protective grounding	<b>Power Consumption</b>	24 kWh/1000h
<b>Rated Input</b>	24 W	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class C.
<b>Rated Input Voltage Frequency</b>	200-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	DALI 2 / DT6		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	4 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	1030 lm		
<b>Rated Angle of Reflection</b>	360 Degree		
<b>Rated Angle of Reflection 2</b>	180 Degree		
<b>Light Distribution</b>	Symmetric		
<b>Distribution Characteristic 120°</b>	NDLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Side, Below		
<b>Height</b>	250 mm		
<b>Diameter</b>	180 mm		
<b>Working Temperature</b>	-30 to 45 °C		
<b>Storage Temperature</b>	-30 to 60 °C		
<b>IP Protection Class</b>	IP 65		