



Special features

- Including 2 plastic panes transparent/satin-finished
- High colour reproduction value

Housing Material	Aluminium
Housing Color	White
Material of Lens	Plastic
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	37 W
Rated Input Voltage	35 V/DC
Rated Current	1050 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	0.2 m
Dimmable	Yes
Control technology	Dimmable via optional power supply unit
Motion Detector	No

Product weight	1420 g
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 20
Life Time L70 / B50	40000 h
Switching Cycles	100000
Power Consumption	37 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	3000 lm
Luminous Efficiency	81.1 lm/W
Rated Angle of Reflection	60 Degree
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	99 mm
Diameter	230 mm
Installation Depth	99 mm
Cut Out Diameter	210 mm

