

## Han-Eco Mod.10-C-f. HTE/HSE



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 19 41 010 5406  |
| Specification      | Han-Eco Mod.10-C-f. HTE/HSE   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19410105406">https://b2b.harting.com/19410105406</a> |

### Identification

|                             |                  |
|-----------------------------|------------------|
| Category                    | Accessories      |
| Series of hoods/housings    | Han-Eco® Modular |
| Type of hood/housing        | Protection cover |
| Description of hood/housing | for hoods        |

### Version

|              |                      |
|--------------|----------------------|
| Size         | 10 B                 |
| Locking type | Double locking lever |

### Technical characteristics

|  |                 |
|--|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Number of relockings                   | ≥500            |
| Degree of protection acc. to IEC 60529 | IP65            |

### Material properties

|   |  |
|---|--|
| Material (hood/housing)                   | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (hood/housing)                     | RAL 9005 (jet black)                     |
| Material (seal)                           | NBR                                      |
| Colour (seal)                             | RAL 9005 (jet black)                     |
| Material (locking)                        | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (locking)                          | RAL 9005 (jet black)                     |
| Material flammability class acc. to UL 94 | V-0                                      |



**Pushing Performance**  
Since 1945

## Material properties

|  |                              |
|--|------------------------------|
| Material flammability class acc. to UL 94 (locking levers) | V-0                          |
| RoHS   | compliant                    |
| ELV status   | compliant                    |
| China RoHS   | e                            |
| REACH Annex XVII substances                                | Not contained                |
| REACH ANNEX XIV substances                                 | Not contained                |
| REACH SVHC substances                                      | Not contained                |
| Fire protection on railway vehicles                        | EN 45545-2 (2020-08)         |
| Requirement set with Hazard Levels                         | R22 (HL 1-3)<br>R23 (HL 1-3) |

## Specifications and approvals

|                |   |
|----------------|---|
| Specifications | IEC 61984<br>EN 45545-2 Fire protection on railway vehicles |
| UL / CSA       | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076  |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1                                      |
| Net weight                     | 70.5 g                                 |
| Country of origin              | Germany                                |
| European customs tariff number | 85389099                               |
| GTIN                           | 5713140130951                          |
| eCl@ss                         | 27440208 Cap for industrial connectors |