



**Special features**

- Particularly impact-resistant
- Feed-through wiring possible
- Light direction infinitely adjustable
- IP68-certified

<b>Housing Material</b>	Plastic
<b>Housing Color</b>	White
<b>Housing Surface</b>	Matt
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	21 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Rated Current</b>	80 mA
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	No
<b>Motion Detector</b>	No

<b>Life Time L70 / B50</b>	50000 h
<b>Switching Cycles</b>	25000
<b>Power Consumption</b>	21 kWh/1000h
<b>Energy Efficiency Class</b>	E

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	5000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	2265 lm
<b>Rated Angle of Reflection</b>	100 Degree
<b>Light Distribution</b>	Symmetric
<b>Distribution Characteristic 120°</b>	NDLS

<b>Swivel Angle</b>	360 Degree
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

<b>Height</b>	700 mm
<b>Diameter</b>	39 mm

<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-40 to 70 °C
<b>IP Protection Class</b>	IP 68/max. 2 m
<b>IK Protection Class</b>	IK10

