

## Connector - with screwless terminals, for harsh applications



| Product description       |                            |
|---------------------------|----------------------------|
| BALS-Prd.-Nr              | 31884                      |
| EAN                       | 4024941318846              |
| Product category          | Connector QUICK-CONNECT TE |
| Current                   | 32A                        |
| Number of poles           | 5p                         |
| Poles                     | 3p+N+PE                    |
| Position of earth contact | 7 h                        |
| Voltage                   | 277/480 up to 288/500V     |

| Product description    |  |
|------------------------|--|
| Frequency              | 50 and 60Hz  |
| Protection degree      | IP44   |
| Colour code            | black RAL 9005   |
| Colour of appliance    | Enclosure black RAL 9005, Hinged lid black RAL 9005, Cable gland grey RAL 7035                           |
| Connection design      | screwless spring terminals as cage clamp with Kontex-contact   |
| Maximum conductor size | 6,0 qmm  |
| Cable entry            | Cable gland  |
| Height                 | 199mm  |
| Width                  | 72mm   |
| Depth                  | 99mm   |
| Material of enclosure  | Polyamide  |
| Contact                | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties |  |
|---------------------------------|--|
|                                 | For cable diameter from 13 up to max. 27 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.321 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |

| Logistics data |               |
|----------------|---------------|
| EAN            | 4024941318846 |
| Length         | 99 mm         |
| Width          | 72 mm         |
| Height         | 199 mm        |
| Weight         | 0.322 kg      |
| Volume         | 1,418.472 ccm |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941823814 |
| Length         | 325 mm        |
| Width          | 217 mm        |
| Height         | 210 mm        |
| Weight         | 3.416 kg      |
| Volume         | 13,588.4 ccm  |



| Ampere                     | 16    | 16    | 16    | 32    | 32    | 32    |
|----------------------------|-------|-------|-------|-------|-------|-------|
| Polzahl                    | 3     | 4     | 5     | 3     | 4     | 5     |
| a ø                        | 51,0  | 58,0  | 65,0  | 66,5  | 66,5  | 72,0  |
| b                          | 156,0 | 162,0 | 168,0 | 195,0 | 195,0 | 198,0 |
| c                          | 72,0  | 78,0  | 86,0  | 89,0  | 89,0  | 99,0  |
| d ø                        | 18,0  | 18,0  | 21,0  | 23,0  | 23,0  | 27,0  |
| Leiter mm <sup>2</sup> min | 1     | 1     | 1     | 2,5   | 2,5   | 2,5   |
| Leiter mm <sup>2</sup> max | 2,5   | 2,5   | 2,5   | 6     | 6     | 6     |
|                            |       |       |       |       |       |       |
|                            |       |       |       |       |       |       |
|                            |       |       |       |       |       |       |
|                            |       |       |       |       |       |       |

3 MB 62