



Special features

- Suitable for workplaces with screens
- Very low glare value
- Particularly energy efficient

Housing Material	Aluminium	IK Protection Class	IK03
Housing Color	White	Life Time L70 / B50	50000 h
Material of Lens	Plastic	Switching Cycles	100000
Protection Class	Protection class III/safety extra-low voltage	Power Consumption	17 kWh/1000h
Operating Mode	Constant current	Energy Efficiency Class	D
Rated Input	17 W		
Rated Input Voltage	35-40 V/DC		
Rated Current	450 mA		
Power Supply Unit incl.	No		
Secondary Connection	Open cables		
Dimmable	Yes		
Control technology	Dimmable via optional power supply unit		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	3200 lm		
Luminous Efficiency	188.2 lm/W		
Rated Angle of Reflection	90 Degree		
UGR	19		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	620 mm		
Width	620 mm		
Height	32 mm		
IP Protection Class	IP 40		