





Due to their flexible control options, you can use the D PROFESSION pendant lamps both in private and in commercial applications. In private settings, the dimmable Down version creates an exceptional atmosphere of illumination that blends perfectly with its modern design.

Special features

- High light output
- Very low glare value
- Dimmable
- Max. suspended mounting 3,000 mm

Housing Material	Aluminium
Housing Color	Silver
Material of Lens	Plastic
Protection Class	Protection class I/protective grounding
Rated Input	28 W
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	DALI 1 / DT6
Motion Detector	No

Working Temperature	-20 to 40 °C
Storage Temperature	-30 to 60 °C
IP Protection Class	IP 20

Life Time L70 / B50	50000 h
Switching Cycles	25000
Power Consumption	28 kWh/1000h
Energy Efficiency Class	D

Light Source	LED, Light source not changeable
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	3165 lm
Rated Angle of Reflection	24 Degree
UGR	19
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	1177.4 mm
Width	53 mm
Height	53 mm
Base length	560 mm
Base width	65 mm
Base height	38 mm
Pendulum Length max.	3000 mm

