



Special features

- Base L x W x H: 145 x 145 x 20 mm

Housing Material	Die-cast aluminium	IP Protection Class	IP 65
Housing Color	Grey	Life Time L70 / B50	30000 h
Material of Lens	Plastic	Switching Cycles	20000
Protection Class	Protection class I/protective grounding	Power Consumption	13 kWh/1000h
Rated Input	13 W	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Rated Input Voltage Frequency	100-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Cable Primary	Yes		
Primary Connection	Connection box IP65		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	950 lm		
Light Distribution	Symmetric		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	1		
Light characteristics	Indirect		
Light direction	Below		
Length	151 mm		
Width	151 mm		
Height	500 mm		
Base length	145 mm		
Base width	145 mm		
Base height	20 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-10 to 60 °C		