



The UNI II series includes high-quality surface-mounted lamps for use on walls and ceilings in commercial and private spaces. The rotatable and swivelling lamp heads have warm white COB LEDs and if required can be folded flush to the mount to shine vertically downwards like a ceiling spotlight. In addition to the single, double and triple designs, there is both a mini version (with smaller lamp head and mount) and a MAX version available. There is also a variant for use in current tracks.

Special features

- High colour rendering
- Can be rotated and swivelled
- Dimmable

Housing Material	Die-cast aluminium	IP Protection Class	IP 20
Housing Color	White	Life Time L70 / B50	20000 h
Material of Lens	Plastic	Switching Cycles	15000
Protection Class	Protection class I/protective grounding	Power Consumption	32 kWh/1000h
Rated Input	32 W	Energy Efficiency Class	G
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	Yes		
Control technology	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	2410 lm		
Rated Angle of Reflection	36 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Swivel Angle	90 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	128 mm		
Diameter	125 mm		
Base height	62 mm		
Base diameter	125 mm		
Working Temperature	-5 to 40 °C		
Storage Temperature	-20 to 50 °C		