



The power supply unit series with up to 240 W and a cross-section of just 32 x 23 mm has impressive output potential under its „bonnet“! This power supply unit is therefore suitable for most ceiling covers, shadow gaps or any other installation situations where space is limited.

#### Special features

- Compact design
- Flicker-free
- Short-circuit-proof, overload protection, overheating protection
- Ideal for installation in ceiling covers

<b>Housing Material</b>	Plastic
<b>Housing Color</b>	Black
<b>Operating Mode</b>	Constant voltage
<b>Protection Class</b>	Protection class II/protective insulation
<b>Power</b>	240 W
<b>Output Voltage</b>	24 V/DC
<b>Output Current</b>	0-10000 mA
<b>Power Factor</b>	0.95
<b>Connection Type</b>	Clamp
<b>Number of Circuit Breaker B10A max.</b>	1
<b>Number of Circuit Breaker B16A max.</b>	2
<b>Number of Circuit Breaker C10A max.</b>	3
<b>Number of Circuit Breaker C16A max.</b>	5
<b>Inrush Current max.</b>	120 A / 500 $\mu$ s
<b>Capacitive Load</b>	5600 $\mu$ F
<b>Reference Point Tc</b>	80 °C
<b>Working Temperature</b>	-20 to 45 °C
<b>Storage Temperature</b>	-20 to 45 °C
<b>IP Protection Class</b>	IP 20
<b>Life Time</b>	30000 h
<b>Length</b>	357 mm
<b>Width</b>	32 mm
<b>Height</b>	23 mm
<b>Product weight</b>	350 g

