

Connector - with screwless terminals, for harsh applications



| Product description | |
|---------------------------|----------------------------|
| BALS-Prd.-Nr | 31309 |
| EAN | 4024941313094 |
| Product category | Connector QUICK-CONNECT TE |
| Current | 32A |
| Number of poles | 4p |
| Arrangement of phases | 3P+PE |
| Position of earth contact | 4 h |
| Voltage | 100 - 130V~ |

| Product description | |
|------------------------|--|
| Frequency | 50/60Hz |
| Protection degree | IP67 |
| Colour code | yellow RAL 1012 |
| Colour of appliance | Hinged lid yellow RAL 1012, Enclosure yellow RAL 1012, Bayonet ring grey RAL 7035, Cable gland grey RAL 7035 |
| Connection design | screwless spring terminals as cage clamp with Kontex-contact |
| Maximum conductor size | 6,0 qmm |
| Cable entry | Cable gland |
| Height | 198mm |
| Width | 94mm |
| Depth | 97mm |
| Material of enclosure | Polyamide |
| Contacts | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties | |
|---------------------------------|--|
| | For cable diameter from 11 up to max. 23,5 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.375 kg / Piece |
| Packaging | Bag |

| Logistics data | |
|----------------|---------------|
| Content amount | 1 ST |
| EAN | 4024941313094 |
| Length | 97 mm |
| Width | 94 mm |
| Height | 198 mm |
| Weight | 0.376 kg |
| Volume | 1,805.364 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941835084 |
| Length | 325 mm |
| Width | 217 mm |
| Height | 210 mm |
| Weight | 3.956 kg |
| Volume | 13,588.4 ccm |

