

PRODUCTS REFERENCES

Références	Désignations	Code EAN	Dimensions / Poids du pack.
1870702	V500 PRO io Door Phone DIN Rail Power Supply	3660849582821	376 x 282 x 85 mm / TBD
1870703	V500 PRO io Door Phone Plug Power Supply	3660849582838	376 x 282 x 85 mm / TBD
1870655	V500 PRO io Indoor Monitor	3660849582388	TBD
9026469	DIN Rail Power Supply 24V	3660849581268	TBD
9020341	Plug Power Supply 24V	3660849540968	TBD

TECHNICAL SPECIFICATIONS

Max nbr of equipments per installation	1 call station and 2 monitors
Distance between call station and monitor	150 m maximum
Installation mode	Installation with 2 wires / 2 power modes available : DIN rail or mains socket
INDOOR MONITOR	
Use	Indoor
Screen	Touch screen 7" / Resolution : 800 x 480 pixels
Audio	Integrated loudspeaker & microphone
Image memory and melody	16 Gb (micro SD card supplied)
Main settings	Melody (x 7 + 1 customisable with micro SD card), ring volume, colour, contrast, light, audio volume, screen display, a adjustment of outdoor temperature, time and date
Other functions	Integrated movement detector for a automatic ON of the monitor (deactivable function)
Fixing	Surface-mounted with supplied wall mounting bracket
Mains	100-240 V / 50-60 Hz 0,6A 24Vdc 1 A DIN rail module or power adaptor for mains socket
Material	Glass and plastics
Functioning temperature	-10°C to 55°C
Dimensions	230 x 172 x 22 mm
CALL STATION	
Use	Outdoor
View angle	H : 102° / V : 65°
Night vision	Infrared LEDs
Outputs	1 dry contact for gate 1 output for strike/electrical lock 12V 800 mA (opening time setting: 2, 5 or 10 s)
Radio	Radio range : 200 m (in free field) Radio frequency: io : 868 – 870 MHz (1-way)
Other functions	Integrated outdoor temperature sensor
Fixing	Projecting with supplied wall mounting
Material	Aluminium and plastics
Functioning temperature	-20°C to 55°C
Dimensions	78 x 146 x 46 mm