



Product Features

- Plug-in extension module for <R>-Control Plus IP 8 and <R>-Control Plus IP 4
- for DIN-rail mounting (72 mm)
- protection class IP20
- integrated power supply: 100 V-240V AC/50-60 Hz
- power consumption: 5 VA max.
- temperature range -5°C to +40°C
- 4 switching outputs 16A/230V (cos phi = 1, detachable, screwless plug-in terminal up to 2,5mm²)
- switching outputs configurable for roller blinds (max.2)
- 4 analog outputs 0-10 V for dimm applications
- extensive logic functions for linking all input parameters such as:
 - AND/OR links of the inputs
 - time switching functions (annual time switch), with random generator
 - alarming functions by mail
 - and much more
- configuration via web browser by <R>-Control Plus IP 8 or <R>-Control Plus IP 4
- SmartPhone control via free of charge App (iOs/Android)
- UDP protocol assistance for all functions/parameters
- API interface for all functions/parameter
- operator guidance at languages D/GB/NL/F
- UDP-protocol for controlling all functions/parameter
- API-interface for controlling all functions/parameter
- operator guidance at languages D/GB/NL/F

Features

General	
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921665886
Mounting types	
DIN-Rail	Yes
Dimensions/Weights without packaging	
Length mm	90
Width mm	72
Height mm	59
Net weight piece kg	0,192

Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,26
Packaging unit Width mm	116
Packaging unit Height mm	76
Packaging unit Depth mm	100
References	
Accessories	700802611, 700802615

