



<b>Housing Material</b>	Stainless steel
<b>Housing Color</b>	Silver
<b>Housing Surface</b>	Brushed
<b>Material of Lens</b>	Glass
<b>Surface Structure of Lens</b>	Transparent
<b>Protection Class</b>	Protection class III/safety extra-low voltage
<b>Operating Mode</b>	Constant voltage
<b>max. Power</b>	1x max. 35 W
<b>Rated Input Voltage</b>	12 V/AC/DC
<b>Socket Description</b>	GU5.3 / MR16
<b>Socket Quantity</b>	1
<b>Power Supply Unit incl.</b>	No
<b>Connection Cable Secondary</b>	Yes
<b>Secondary Connection</b>	Open cables
<b>Dimmable</b>	Yes
<b>Control technology</b>	Dimmable via optional light source
<b>Motion Detector</b>	No
<b>Execution</b>	Without lamp
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below
<b>Height</b>	35 mm
<b>Diameter</b>	85 mm
<b>Installation Depth</b>	60 mm
<b>Cut Out Diameter</b>	55 mm
<b>Product weight</b>	113 g
<b>Working Temperature</b>	-5 to 40 °C
<b>IP Protection Class</b>	IP 44