

**Special features**

- Base L x W x H: 165 x 165 x 25 mm

|   |   |                                |              |
|---|---|--------------------------------|--------------|
| <b>Housing Material</b>                 | Die-cast aluminium                      | <b>Life Time L70 / B50</b>     | 30000 h      |
| <b>Housing Color</b>                    | Grey                                    | <b>Switching Cycles</b>        | 15000        |
| <b>Material of Lens</b>                 | Plastic                                 | <b>Power Consumption</b>       | 18 kWh/1000h |
| <b>Protection Class</b>                 | Protection class I/protective grounding | <b>Energy Efficiency Class</b> | G            |
| <b>Rated Input</b>                      | 18 W                                    |                                |              |
| <b>Rated Input Voltage Frequency</b>    | 110-240 V/AC 50 / 60 Hz                 |                                |              |
| <b>Power Supply Unit incl.</b>          | Yes                                     |                                |              |
| <b>Connection Type</b>                  | Clamp                                   |                                |              |
| <b>Dimmable</b>                         | No                                      |                                |              |
| <b>Motion Detector</b>                  | No                                      |                                |              |
| <b>Light Source</b>                     | LED, Light source not changeable        |                                |              |
| <b>Color Temperature</b>                | 3000 K                                  |                                |              |
| <b>Colour Consistency</b>               | 6 SDCM                                  |                                |              |
| <b>Colour Rendering Index (Ra)</b>      | 80                                      |                                |              |
| <b>Rated Luminous Flux</b>              | 1300 lm                                 |                                |              |
| <b>Rated Angle of Reflection</b>        | 120 Degree                              |                                |              |
| <b>Distribution Characteristic 120°</b> | NDLS                                    |                                |              |
| <b>Light Exit Surfaces</b>              | 1                                       |                                |              |
| <b>Light characteristics</b>            | Direct, Indirect                        |                                |              |
| <b>Light direction</b>                  | Top, Below, Side, Rear                  |                                |              |
| <b>Length</b>                           | 300 mm                                  |                                |              |
| <b>Width</b>                            | 300 mm                                  |                                |              |
| <b>Height</b>                           | 47 mm                                   |                                |              |
| <b>Base length</b>                      | 165 mm                                  |                                |              |
| <b>Base width</b>                       | 165 mm                                  |                                |              |
| <b>Base height</b>                      | 25 mm                                   |                                |              |
| <b>Working Temperature</b>              | -5 to 40 °C                             |                                |              |
| <b>Storage Temperature</b>              | -10 to 60 °C                            |                                |              |
| <b>IP Protection Class</b>              | IP 65                                   |                                |              |