




Housing Material	Aluminium, Stainless steel	Storage Temperature	-10 to 40 °C
Housing Color	White	IP Protection Class	IP 40
Functions	Leuchte kann mit Gleichstrom aus einer Zentralbatterie eines Notstromsystems betrieben werden.	Life Time L70 / B50	50000 h
		Life Time L80 / B20	50000 h
		Switching Cycles	100000
		EEL	E
Protection Class	Protection class I/protective grounding		
Protection Class Lamp	Protection class III/safety extra-low voltage		
Power Selectable	32 W, 35.5 W, 38 W, 42 W		
Rated Power Consumption Standby	0.5 W		
Rated Input Voltage Frequency	198-264 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Dimmable	Yes		
Control	Trailing-edge dimmer, Leading-edge dimmer		
Motion Detector	No		
Voltage range emergency lighting	176-280 V/DC		
EOFI	95 %		
Light Source	LED, Light source not changeable		
Color Temperature	3000/4000 K		
Colour Consistency	3 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	5200/5400 lm		
Rated Angle of Reflection	90 Degree		
UGR	19		
Length	1525 mm		
Width	325 mm		
Height	48 mm		
Working Temperature	-10 to 40 °C		