




LED recessed spot INDIWO83, pivoted
Artikel-Nr. 12276153



LED recessed spot INDIWO83, pivoted, nickel, round. In a compact design, for installation in tool-less rapid assembly systems. Recessed spotlight suitable for direct mounting on normally flammable building materials. Thermal insulation allowed. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 6W, Amount of light sources / fittings: 1 Qty, Luminous flux: 520lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 36°, Adjustability: Pivoted, With control gear: No, Control: Dimming depending on driver.

| | |
|--------------------|------------------|
| Artikel-Nr. | 12276153 |
| Stand: | 25.10.2021 22:09 |

| | |
|------------------------------------|-----------------------------|
| Colour temperature | 3000 K |
| Colour | Nickel |
| Beam angle | 36 ° |
| Amount of light sources / fittings | 1 Qty |
| Material | Aluminium / Steel / Plastic |
| Lamp holder | Plug&Play |
| Power | 6 W |
| Lamp | LED |
| Colour rendering | CRI > 80 |
| Control | Dimming depending on driver |

| | |
|----------------------|-------------------|
| Outer diameter | 95 mm |
| Built-in diameter | 83 mm |
| Installation depth | 38 mm |
| Current | 350 mA |
| Degree of protection | IP20 |
| Protection class | III |
| Adjustability | Pivoted |
| Swivel angle | 25 ° |
| Circuit type | Series conduction |