

**Special features**

- Base L x W x H: 100 x 77 x 67 mm

Housing Material	Die-cast aluminium	Storage Temperature	-10 to 60 °C
Housing Color	Grey	IP Protection Class	IP 54
Material of Lens	Glass	Life Time L70 / B50	30000 h
Protection Class	Protection class I/protective grounding	Switching Cycles	100000
Rated Input	15.9 W	Power Consumption	16 kWh/1000h
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Energy Efficiency Class	G
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	510 lm		
Rated Angle of Reflection	360 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Side		
Length	260 mm		
Width	120 mm		
Height	181 mm		
Diameter	120 mm		
Base length	100 mm		
Base width	77 mm		
Base height	67 mm		
Working Temperature	-20 to 40 °C		