

## Wall mounting appliance inlet - with closure cap




| Product description       |                               |
|---------------------------|-------------------------------|
| BALS-Prd.-Nr              | 2490                          |
| EAN                       | 4024941024907                 |
| Product category          | Wall mounting appliance inlet |
| Current                   | 16A                           |
| Number of poles           | 4p                            |
| Poles                     | 3P+PE                         |
| Position of earth contact | 7 h                           |
| Voltage                   | 480 up to 500V                |
| Frequency                 | 50 and 60Hz                   |

| Product description    |   |
|------------------------|---|
| Protection degree      | IP67  |
| Colour code            | black RAL 9005  |
| Colour of appliance    | Closure cap grey RAL 7035, Collar black RAL 9005, Bayonet ring grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035 |
| Connection design      | with screw terminal   |
| Maximum conductor size | 2,5 qmm   |
| Cable entry            | top entry M20   |
| Height                 | 151mm   |
| Width                  | 79mm  |
| Depth                  | 120mm   |
| Dimension of enclosure | 100x75 mm (HxW)   |
| Material of enclosure  | Polyamide   |
| Contact                | The contact carrier is made of polyamide, the contacts are brass nickel plated  |

| Additional technical properties |   |
|---------------------------------|---|
|                                 | The cable entry is one at top open and one at bottom and one rear side closed |
|                                 | With closure cap  |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.288 kg / Piece |
| Packaging      | Bag              |

| Logistics data |               |
|----------------|---------------|
| Content amount | 1 ST          |
| EAN            | 4024941024907 |
| Length         | 120 mm        |
| Width          | 79 mm         |
| Height         | 151 mm        |
| Weight         | 0.289 kg      |
| Volume         | 1,431.48 ccm  |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941832885 |
| Length         | 325 mm        |
| Width          | 217 mm        |
| Height         | 210 mm        |
| Weight         | 3.086 kg      |
| Volume         | 13,588.4 ccm  |



| Ampere  | 16    | 16      | 16      | 32    | 32    | 32    |
|---------|-------|---------|---------|-------|-------|-------|
| Polzahl | 3     | 4       | 5       | 3     | 4     | 5     |
| a       | 64,0  | 75,0    | 84,0    | 90,0  | 90,0  | 90,0  |
| b       | 87,0  | 100,0   | 84,0    | 75,0  | 75,0  | 75,0  |
| c       | 137,0 | 151,0   | 137,0   | 147,0 | 147,0 | 148,0 |
| d       | 112,0 | 119,0   | -       | 122,0 | 122,0 | 123,0 |
| e       | 51,0  | 59,0    | -       | -     | -     | -     |
| f       | -     | 11,0    | -       | -     | -     | -     |
| h ø     | 4,1   | 5,1     | -       | -     | -     | -     |
| i       | 4,5   | 4,5     | -       | -     | -     | -     |
| k       | 40,0  | -       | -       | -     | -     | -     |
| l       | -     | -       | 111,0   | -     | -     | -     |
| m       | -     | -       | 64,0    | 78,0  | 78,0  | 78,0  |
| n       | -     | -       | 64,0    | 45,0  | 45,0  | 45,0  |
| o ø     | -     | -       | 5,5     | 5,5   | 5,5   | 5,5   |
| p       | M20   | M20     | -       | -     | -     | -     |
| r       | -     | -       | M20     | M25   | M25   | M25   |
| s ø     | -     | -       | 23,0    | 29,0  | 29,0  | 29,0  |
| t       | -     | für M20 | für M20 | -     | -     | -     |