

## Han 48M-HBM-SL




Image is for illustration purposes only. Please refer to product description.

Part number	09 37 048 0302
Specification	Han 48M-HBM-SL
HARTING eCatalogue	<a href="https://b2b.harting.com/09370480302">https://b2b.harting.com/09370480302</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> M
Type of hood/housing	Bulkhead mounted housing
Type	Low construction

### Version

Size	48 B
Locking type	Single locking lever
Field of application	Hoods/housings for rough environments

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	FPM
Material (locking)	Stainless steel



**Pushing Performance**  
Since 1945

## Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes

## Commercial data

Packaging size	1
Net weight	505.04 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140171398
eCl@ss	27440202 Shell for industrial connectors