



| | |
|-----------------------------------|---|
| Housing Material | Copper |
| Housing Color | White |
| Protection Class | Protection class III/safety extra-low voltage |
| Operating Mode | Constant voltage |
| Rated Input 1m | 22.5 W |
| Rated Input Voltage | 24 V/DC |
| Power Supply Unit incl. | No |
| Connection Cable Primary | Yes |
| Primary Connection | With free strand / conductor ends |
| Primary Cable Length | 1 m |
| Connection Cable Secondary | Yes |
| Secondary Connection | Open cables |
| Secondary Cable Length | 1 m |
| Dimmable | Yes |
| Control technology | Dimmable via optional controller |

| | |
|--------------------------------|--------------|
| Height | 2 mm |
| Product weight | 122 g |
| Working Temperature | -15 to 50 °C |
| Storage Temperature | -10 to 60 °C |
| IP Protection Class | IP 20 |
| Life Time L70 / B50 | 60000 h |
| Switching Cycles | 30000 |
| Power Consumption | 75 kWh/1000h |
| Energy Efficiency Class | D |

| | |
|---|----------------------------------|
| Light Source | LED, Light source not changeable |
| Lightcolor | Neutral white |
| Color Temperature | 4000 K |
| Colour Consistency | 6 SDCM |
| Colour Rendering Index (Ra) | 90 |
| Rated Angle of Reflection | 110 Degree |
| Luminous Flux 1m | 2815 lm |
| Luminous Efficiency 1m | 125.11 lm/W |
| LED/Meter | 160 |
| Bending Radius min. | 20 mm |
| Total Length to be Operated max. | 5 m |
| Segment Length | 50 mm |
| Segment LED Quantity | 8 |
| LED Distance | 6.25 mm |

| | |
|---------------|---------|
| Length | 5000 mm |
| Width | 10 mm |