



| | | | |
|---|---|--------------------------------|--------------|
| Housing Material | Copper | Length | 50000 mm |
| Housing Color | White | Width | 10 mm |
| Protection Class | Protection class III/safety extra-low voltage | Height | 3 mm |
| Operating Mode | Constant voltage | Product weight | 1340 g |
| Rated Input 1m | 19 W | Working Temperature | -15 to 50 °C |
| Rated Input Voltage | 24 V/DC | Storage Temperature | -10 to 60 °C |
| Power Supply Unit incl. | No | IP Protection Class | IP 20 |
| Connection Cable Primary | Yes | Life Time L70 / B50 | 30000 h |
| Primary Connection | With free strand / conductor ends | Switching Cycles | 100000 |
| Primary Cable Length | 1 m | Power Consumption | 19 kWh/1000h |
| Connection Cable Secondary | Yes | Energy Efficiency Class | G |
| Secondary Connection | Open cables | | |
| Secondary Cable Length | 1 m | | |
| Dimmable | Yes | | |
| Control technology | Dimmable via optional controller | | |
| Number of Channels | 1 | | |
| Light Source | LED, Light source not changeable | | |
| Lightcolor | Warm white (WW) | | |
| Color Temperature | 3000 K | | |
| Colour Consistency | 6 SDCM | | |
| Colour Rendering Index (Ra) | 90 | | |
| Rated Angle of Reflection | 120 Degree | | |
| Distribution Characteristic 120° | DLS | | |
| Luminous Flux 1m | 1605 lm | | |
| Luminous Efficiency 1m | 84.47 lm/W | | |
| LED/Meter | 240 | | |
| Bending Radius min. | 20 mm | | |
| Total Length to be Operated max. | 5 m | | |
| Segment Length | 25 mm | | |
| Segment LED Quantity | 6 | | |
| LED Distance | 4.16 mm | | |