

DSUB SV FE SSDP ANG73-254 37P PL2 HOLE




Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 66 412 6600 |
| Specification | DSUB SV FE SSDP ANG73-254 37P PL2 HOLE |
| HARTING eCatalogue | https://b2b.harting.com/09664126600 |

Identification

| | |
|----------------------------|-------------------|
| Category | Connectors |
| Series | D-Sub |
| Identification | Standard |
| Element | Connector |
| Description of the contact | Stamped Angled |

Version

| | |
|--------------------|---|
| Termination method | Wave soldering termination |
| Gender | Female |
| Size | D-Sub 4 |
| Connection type | Motherboard to daughtercard |
| Number of contacts | 37 |
| Termination length | 2.9 mm |
| Locking type | Fixing flange with feed through hole \varnothing 3.1 mm |

Technical characteristics

| | |
|------------------------------------|---------------------|
| Distance between rows | 2.54 mm |
| Contact spacing (termination side) | 2.76 mm |
| Rated current | 6.5 A |
| Clearance distance | ≥ 1 mm |
| Creepage distance | ≥ 1 mm |
| Insulation resistance | $>10^{10}$ Ω |



Pushing Performance
Since 1945

Technical characteristics

| | |
|---------------------------|-----------------------------|
| Contact resistance | ≤10 mΩ |
| Limiting temperature | -55 ... +125 °C |
| Insertion force | ≤123 N |
| Withdrawal force | ≥11 N ≤82 N |
| Performance level | 2 acc. to CECC 75301-802 |
| Mating cycles | ≥250 |
| Test voltage $U_{r.m.s.}$ | 1 kV |
| Isolation group | IIIa (175 ≤ CTI < 400) |
| PCB thickness | ≥1.6 mm |
| Installation height | 7.3 mm |
| Hot plugging | No |

Material properties

| | |
|---|---|
| Material (insert) | Thermoplastic resin, glass-fibre filled (PBTP) Shell: Plated steel |
| Colour (insert) | Black |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Noble metal over Ni |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Antimony trioxide Nickel |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

| | |
|----------------|-----------|
| Specifications | DIN 41652 |
|----------------|-----------|



Pushing Performance
Since 1945

Specifications and approvals

UL / CSA UL 1977 ECBT2.E102079

Commercial data

| | |
|--------------------------------|------------------------|
| Packaging size | 100 |
| Net weight | 19.3 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |
| GTIN | 5713140221062 |
| eCl@ss | 27440214 D-Sub coupler |
