

**Special features**

- Very low glare value
- Service life 50,000 h L80B10
- Dimmable using touch sensor
- Ready to use

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Silver
<b>Material of Lens</b>	Acryl
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	55 W
<b>Rated Input Voltage</b>	200-240 V/AC 50 / 60 Hz
<b>Frequency</b>	
<b>Power Supply Unit incl.</b>	No
<b>Connection Cable Primary</b>	Yes
<b>Primary Connection</b>	Power plug
<b>Primary Cable Length</b>	2.5 m
<b>Connection Type According to Standard</b>	Typ Y
<b>Dimmable</b>	Yes
<b>Control technology</b>	Touch-Sensor
<b>Motion Detector</b>	No

<b>Width</b>	310 mm
<b>Height</b>	1950 mm
<b>Base length</b>	500 mm
<b>Base width</b>	225 mm
<b>Product weight</b>	11900 g
<b>Working Temperature</b>	-20 to 45 °C
<b>Storage Temperature</b>	-40 to 80 °C
<b>IP Protection Class</b>	IP 20

<b>Life Time L70 / B50</b>	50000 h
<b>Life Time L80 / B10</b>	50000 h
<b>Switching Cycles</b>	25000
<b>Power Consumption</b>	55 kWh/1000h
<b>Energy Efficiency Class</b>	E

<b>Light Source</b>	LED, Light source not changeable
<b>Lightcolor</b>	Neutral white
<b>Color Temperature</b>	4000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	6245 lm
<b>Luminous Efficiency</b>	113.5 lm/W
<b>Rated Angle of Reflection</b>	150 Degree
<b>Rated Angle of Reflection 2</b>	150 Degree
<b>UGR</b>	19
<b>Distribution Characteristic 120°</b>	NDLS

<b>Light Exit Surfaces</b>	2
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Top, Below

<b>Length</b>	610 mm
---------------	--------

