



| | | | |
|--------------------------------------|---|--|---|
| Housing Material | Aluminium, Polycarbonate, Iron | Life Time L70 / B50 | 30000 h |
| Housing Color | White | Switching Cycles | 20000 |
| Housing Surface | Matt | Power Consumption | 65 kWh/1000h |
| Material of Lens | Acryl | Energy Efficiency Class Lightsource | This product contains light sources of energy efficiency classes E and F. |
| Surface Structure of Lens | Satined | | |
| Protection Class | Protection class I/protective grounding | | |
| Rated Input | 65 W | | |
| Rated Input Voltage Frequency | 220-240 V/AC 50 / 60 Hz | | |
| Power Supply Unit incl. | Yes | | |
| Connection Type | Clamp | | |
| Dimmable | Yes | | |
| Control technology | Leading-edge dimmer, Trailing-edge dimmer | | |
| Motion Detector | No | | |
| Light Source | LED, Light source changeable TC | | |
| Color Temperature | 3000/4000 K | | |
| Colour Consistency | 6 SDCM | | |
| Colour Rendering Index (Ra) | 80 | | |
| Rated Luminous Flux | 5600/6000 lm | | |
| Rated Luminous Flux 2 | 6000 lm | | |
| Light Exit Surfaces | 2 | | |
| Light characteristics | Direct, Indirect | | |
| Light direction | Top, Below | | |
| Height | 90 mm | | |
| Diameter | 600 mm | | |
| Working Temperature | -10 to 45 °C | | |
| Storage Temperature | -10 to 45 °C | | |
| IP Protection Class | IP 20 | | |