



LACERTAE is a light trap - and guaranteed to turn heads. Matching the portable variant, the LACERTAE is also impressive as a rustic wall light with movement sensor on clay brick and natural stone walls.

Special features

- Base L x W x H: 98 x 30 x 105 mm

| | |
|--------------------------------------|---|
| Housing Material | Die-cast aluminium |
| Housing Color | Grey |
| Material of Lens | Glass |
| Protection Class | Protection class I/protective grounding |
| Rated Input | 10 W |
| Rated Input Voltage Frequency | 110-240 V/AC 50 / 60 Hz |
| Power Supply Unit incl. | Yes |
| Connection Type | Clamp |
| Dimmable | No |
| Motion Detector | Yes |
| Kind of Motion Detector | Infrared |
| Detection Distance | 1-10 m |
| Angle of Detection | 120 Degree |

| | |
|----------------------------|--------------|
| Working Temperature | -5 to 40 °C |
| Storage Temperature | -10 to 60 °C |
| IP Protection Class | IP 54 |

| | |
|---|----------------------------------|
| Light Source | LED, Light source not changeable |
| Color Temperature | 3000 K |
| Colour Consistency | 6 SDCM |
| Colour Rendering Index (Ra) | 80 |
| Rated Luminous Flux | 440 lm |
| Rated Angle of Reflection | 120 Degree |
| Distribution Characteristic 120° | NDLS |

| | |
|--------------------------------|--------------|
| Life Time L70 / B50 | 20000 h |
| Switching Cycles | 15000 |
| Power Consumption | 10 kWh/1000h |
| Energy Efficiency Class | G |

| | |
|------------------------------|--------|
| Light Exit Surfaces | 1 |
| Light characteristics | Direct |
| Light direction | Below |

| | |
|--------------------|--------|
| Length | 180 mm |
| Width | 256 mm |
| Height | 370 mm |
| Base length | 98 mm |
| Base width | 30 mm |
| Base height | 105 mm |