

Wall mounting socket outlet, switched and fused - housing dimensions 365x134, with fuse base D



| Product description | |
|---------------------------|--|
| BALS-Prd.-Nr | 17238 |
| EAN | 4024941172387 |
| Product category | Wall mounting socket outlet, switched, fused |
| Current | 32A |
| Number of poles | 4p |
| Poles | 3P+PE |
| Position of earth contact | 7 h |
| Voltage | 480 up to 500V |

| Product description | |
|------------------------|--|
| Frequency | 50 and 60Hz |
| Protection degree | IP67 |
| Colour code | black RAL 9005 |
| Colour of appliance | Hinged lid black RAL 9005, Operating window smoky topaz, Bayonet ring grey RAL 7035, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035, Control knob grey RAL 7035 |
| Connection design | screwless spring terminals as cage clamp with Kontex-contact |
| Maximum conductor size | 10,0 qmm |
| Cable entry | top entry M40/M32 bottom entry M40/32 |
| Height | 400mm |
| Width | 134mm |
| Depth | 154mm |
| Dimension of enclosure | 365x134 mm (HxW) |
| Material of enclosure | Polycarbonate |
| Contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties | |
|---------------------------------|--|
| | cable entry two at top and two at bottom (open) |
| | In 0-position lockable for 3 padlocks with bow diameter up to 7 mm |
| | With fuse base 3 pole D III |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 2.406 kg / Piece |
| Packaging | Carton |
| Content amount | 1 ST |
| EAN | 4024941172387 |
| Length | 387 mm |
| Width | 222 mm |
| Height | 150 mm |
| Weight | 2.599 kg |
| Volume | 11,029.5 ccm |



| Ampere Poles | 16 4 | 16 5 | 32 4 | 32 5 | 63 4 | 63 5 |
|--------------|--------|--------|--------|--------|--------|--------|
| a | 134 | 134 | 134 | 134 | 180 | 180 |
| b | 365 | 365 | 365 | 365 | 460 | 460 |
| c | 117 | 117 | 117 | 117 | 160 | 460 |
| d | 348 | 348 | 348 | 348 | 440 | 440 |
| Øg | 6,5 | 6,5 | 6,5 | 6,5 | 8,3 | 8,3 |
| h | 8 | 8 | 8 | 8 | 6,5 | 6,5 |
| i | M32/25 | M32/25 | M40/32 | M40/32 | M40 | M40 |
| k | M32/25 | M32/25 | M40/32 | M40/32 | M40/32 | M40/32 |
| x | 390 | 390 | 400 | 400 | 503 | 503 |
| y | 134 | 134 | 134 | 134 | 180 | 180 |
| z | 153 | 153 | 154 | 161 | 192 | 192 |