



Housing Material	Aluminium
Housing Color	Silver
Housing Surface	Brushed
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	6 W
Rated Input Voltage	16-17 V/DC
Rated Current	350 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	0.3 m
Dimmable	Yes
Control technology	Dimmable via optional power supply unit
Motion Detector	No

Installation Depth	50 mm
Cut Out Diameter	68 mm
Product weight	144 g
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 20
Life Time L70 / B50	20000 h
Switching Cycles	10000
Power Consumption	6 kWh/1000h
Energy Efficiency Class	E

Light Source	LED, Light source not changeable
Color Temperature	2700 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	580 lm
Luminous Efficiency	96.7 lm/W
Rated Angle of Reflection	45 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	25 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	46 mm
Diameter	78 mm