



- Protection level: IP20  
 - Temperature range:  
 - Fixed installation: -40°C ... +70°C  
 - Dynamic installation: -20°C ... +60°C

**NOTE:**  
 \* For lengths < 1.0m:  
 - relative positioning of the connectors to each other will be as presented in the drawing, however with an admissible angular deviation around cable axis of  $\pm 30^\circ$   
 \* For lengths  $\geq 1.0m$ :  
 - relative positioning of the connectors to each other not obligatory

Cont. no.	Part no.	Type of cable	Dim. a[m]
11	20826311150	HAR PROFINET Typ C 4xAWG 22/7 PUR Trail. green	15 ±0.15
10	20826311100		10 ±0.1
9	20826311050		5 +0.04
8	20826311040		4 +0.04
7	20826311030		3 +0.04
6	20826311020		2 +0.04
5	20826311010		1 +0.04
4	20826311008		0.8 +0.04
3	20826311006		0.6 +0.04
2	20826311004		0.4 +0.02
1	20826311002		0.2 +0.02

	All rights reserved	Created by MUNTEANV Muntean	Inspected by 402676 Gross	Standardisation MUNTEANV Muntean	Date 2023-06-16	State Final Release
	Department HCS - RO	Title RJ45/preLink cable PN Cat.5 4p		Doc-Key / ECM-Nr. 100621724/UGD/000/D 50000245597		
HARTING Customised Solutions D-32339 Espelkamp		Type TB	Number 20826311XXX		Rev. D	Page 1/1