

NOTES:



- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT(500VDC)TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE
HARTING P/N

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
79	AWG 30	79
80	AWG 30	80

HARTING P/N	Cable length(L)
3315 243 010 0123	100 ± 3
3315 243 020 0123	200 ± 5
3315 243 050 0123	500 ± 10

		All Dimensions in mm Original Size DIN A3		Scale 1.5:1	Free size tol. \\	Ref. \		
						Sub. \		
	All rights reserved			Created by ZHENGL	Inspected by WANGE	Standardisation CHENJU	Date 2018-10-12	State Final Release
	Department HCS - CN							
	HARTING Customised Solutions D-32339 Espelkamp			Title Har-Flex 80 Pole,Dul-end,With SR,L=XXMM				Doc-Key / ECM-Nr. 100586986/UGD/000/A 500000141226
Type TB				Number 33150024			Rev. A	Page 1/1