



The ALWA combines two lights into one sophisticated design, a bedside light with indirect shaded light and a reading spotlight. The highlight is the rotatable and swivelling arm (90° tilt angle) by which the ALWA can provide targeted illumination. With its narrow light emission angle of 20°, the ALWA also ensures that anyone else in the bed is guaranteed not to be disturbed.

Special features

- Low light emission angle
- Can be rotated and swivelled
- Ideal as a bedside and reading light

Housing Material	Aluminium
Housing Color	White
Protection Class	Protection class I/protective grounding
Rated Input	3.5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	No
Control technology	Push-Button
Motion Detector	No

IP Protection Class	IP 20
Life Time L70 / B50	30000 h
Power Consumption	4 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	200 lm
Rated Angle of Reflection	20 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	90 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top, Below

Height	110 mm
Diameter	30 mm
Base length	135 mm
Base width	50 mm
Base height	28 mm

Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 40 °C