



Despite the linear design, the Wallwasher - CAPH series assortment is well-rounded. Wallwashers offer a variety of options to accentuate different objects. Whether a rustic stone wall in warm 3,000 K or a modern new build in RGBW. The different visual designs with symmetrical or asymmetrical diffusion angles help with positioning.

With the 230 V variants, no further accessories are required. Thanks to the 24 V versions, the CAPH Wallwashers can be connected to all variants of the control unit on the market.

Special features

- Including connecting cable

Housing Material	Die-cast aluminium	Storage Temperature	-20 to 60 °C
Housing Color	Grey	IP Protection Class Lamp	IP 65
Material of Lens	Glass	IP Protection Class Plug	IP 44
Protection Class	Protection class I/protective grounding	Life Time L70 / B50	30000 h
Rated Input	38 W	Switching Cycles	100000
Rated Input Voltage	220-240 V/AC 50 / 60 Hz	Power Consumption	38 kWh/1000h
Frequency		Energy Efficiency Class	G
Power Supply Unit incl.	Yes		
Connection Cable Primary	Yes		
Primary Connection	Power plug IP44		
Primary Cable Length	2 m		
Connection Type According to Standard	Typ Y		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	3000 lm		
Rated Angle of Reflection	25 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Top		
Length	1000 mm		
Width	53.36 mm		
Height	81.07 mm		
Working Temperature	-20 to 60 °C		