



Housing Material	Die-cast aluminium
Housing Color	Black
Housing Surface	Matt
Material of Lens	Polycarbonate - PC
Surface Structure of Lens	Clear

Working Temperature	-20 to 40 °C
Storage Temperature	-20 to 50 °C
IP Protection Class	IP 65
IK Protection Class	IK04

Protection Class	Protection class III/safety extra-low voltage
Rated Input	2.3 W
Rated Input Voltage	3.7 V/DC
Dimmable	Yes
Control technology	Touch-Sensor
Motion Detector	No
Accumulator/Battery Operated	Yes
Number of Accumulator/Battery	1
Type of Accumulator/Battery	3.7 V lithium ion battery (903050)
Accumulator/Battery Capacity	3000 mAh
Accumulator/Battery Voltage	3.7 V
Accumulator Charging Time	4.5 h
Accumulator Operating Time	8 h

Life Time L70 / B50	20000 h
Power Consumption	3 kWh/1000h

Light Source	LED, Light source changeable TC
Lightcolor	Warm white (WW)
Color Temperature	2200/3000 K
Colour Rendering Index (Ra)	80
Rated Luminous Flux	110 lm
Luminous Efficiency	47.8 lm/W

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	208 mm
Diameter	76 mm
Product weight	437 g