



The ALMAAZ is a classic emergency light with pictogram set to help mark escape routes. As a single-battery light with auto test function, the ALMAAZ, available in flat and tapered designs, performs some of the prescribed DIN functional tests itself and reports faults using an integrated buzzer. Depending on the application, the ALMAAZ can be mounted on the ceiling or on the wall using the rotatable housing. The pictograms supplied indicating escape routes in all directions make the emergency light all the more flexible. Replaceable special pictograms (first aid kit, fire extinguisher) are also optionally available.

Special features

- Recognition range 27 m
- Single-battery technology with LiFePO4 battery
- Ceiling or wall mounting possible
- Auto test function with buzzer
- Including pictogram set

Housing Color	White
Protection Class	Protection class II/protective insulation
Rated Input	3 W
Rated Input Voltage	230 V/AC
Frequency	50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	No
Motion Detector	No
Accumulator/Battery Operated	Yes
Accumulator/Battery Chemical System	Li-Me
Number of Accumulator/Battery	1
Type of Accumulator/Battery	18650
Accumulator/Battery Capacity	1500 mAh
Accumulator/Battery Voltage	3.2 V/DC
Accumulator/Battery Weight	41 g
Light Source	LED, Light source not changeable
Color Temperature	4500 K
Colour Consistency	6 SDCM
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below, Side, Rear
Length	283.4 mm
Width	50 mm
Height	198 mm
Working Temperature	-5 to 35 °C
IP Protection Class	IP 54