



<b>Housing Material</b>	Die-cast aluminium	<b>Light Exit Surfaces</b>	1
<b>Housing Color</b>	White	<b>Light characteristics</b>	Direct
<b>Material of Lens</b>	Plastic	<b>Light direction</b>	Below
<b>Protection Class</b>	Protection class III/safety extra-low voltage	<b>Length</b>	175 mm
<b>Operating Mode</b>	Constant voltage	<b>Width</b>	92 mm
<b>Rated Input</b>	2.2 W	<b>Height</b>	330 mm
<b>Rated Input Voltage</b>	3.7 V/DC	<b>Base length</b>	175 mm
<b>Power Supply Unit incl.</b>	No	<b>Base width</b>	103 mm
<b>Connection Type</b>	USB	<b>Base height</b>	15 mm
<b>Dimmable</b>	Yes	<b>Product weight</b>	1450 g
<b>Control technology</b>	Touch-Sensor	<b>Working Temperature</b>	-20 to 45 °C
<b>Motion Detector</b>	No	<b>Storage Temperature</b>	-40 to 60 °C
<b>Accumulator/Battery Operated</b>	Yes	<b>IP Protection Class</b>	IP 54
<b>Rechargeable/battery included</b>	Yes	<b>Life Time L70 / B50</b>	30000 h
<b>Number of Accumulator/Battery</b>	1	<b>Switching Cycles</b>	15000
<b>Type of Accumulator/Battery</b>	Li-Ion battery type 18650		
<b>Accumulator/Battery Capacity</b>	4400 mAh		
<b>Accumulator/Battery Voltage</b>	3.7 V/DC		
<b>Type of Accumulator/Battery 2</b>	Li-Ion battery type 18650		
<b>Accumulator/Battery Capacity 2</b>	2200 mAh		
<b>Accumulator/Battery Voltage 2</b>	3.7 V/DC		
<b>Number of Accumulator/Battery 2</b>	1		
<b>Accumulator Charging Time</b>	5-7 h		
<b>Accumulator Operating Time</b>	10 h		
<b>Light Source</b>	LED, Light source not changeable		
<b>Lightcolor</b>	Warm white (WW)		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	212 lm		
<b>Luminous Efficiency</b>	96.4 lm/W		
<b>Rated Angle of Reflection</b>	50 Degree		