



**Special features**

- Suitable for workplaces with screens
- Light colour adjustable in 3 stages
- 230 V direct connection
- Including power supply
- Low housing depth

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	White
<b>Protection Class</b>	Protection class II/protective insulation
<b>Rated Input</b>	40 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	Yes
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer
<b>Motion Detector</b>	No

<b>IK Protection Class</b>	IK08
<b>Life Time L70 / B50</b>	30000 h
<b>Switching Cycles</b>	15000
<b>Power Consumption</b>	40 kWh/1000h
<b>Energy Efficiency Class</b>	F

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000/4000/5700 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	90
<b>Rated Luminous Flux</b>	3500 lm
<b>Luminous Efficiency</b>	87.5 lm/W
<b>Rated Angle of Reflection</b>	100 Degree
<b>UGR</b>	19
<b>Distribution Characteristic 120°</b>	DLS

<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

<b>Length</b>	1195 mm
<b>Width</b>	295 mm
<b>Height</b>	10 mm
<b>Product weight</b>	3000 g

<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-20 to 40 °C
<b>IP Protection Class</b>	IP 20