


**LED-light signal**  
**pure white high-gloss****Product Data Sheet**

Assembly arrangement	Basic element with central cover plate
Lamp holder	Other
Mounting method	Flush mounted (plaster)
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface finishing	Glossy
Colour	White
Suitable for degree of protection (IP)	IP20
Nominal voltage	250Volt
Max. lamp power	0.6Watt

**LED-light signal  
pure white high-gloss**

LED-light signal; White LED-light signal with radiating surface 42 x 42 mm,  
writable with film 45 x 45 mm (visible surface 42 x 42 mm).  
Various printed films on request (customer-specific labelling).

Technical data:

Supply voltage: 230 V, 50 Hz, Energy absorption: 0.6 W, Lifetime: > 50,000 hours  
Connection via clamp terminals, cross-connection for connection max. 2.5 mm<sup>2</sup>.

Material No.	Article No.	EAN-code
00025613	D 20.490.022 LED/2	4010105025613

---

**PEHA Elektro GmbH & Co.KG**

a Honeywell Company  
Daimlerstraße 4  
58553 HALVER  
DEUTSCHLAND

Tel.: 02353 9118 001  
Fax: 02353 9118 311  
mail: [peha@honeywell.com](mailto:peha@honeywell.com)  
[www.peha.de](http://www.peha.de)

Änderungen vorbehalten. © Honeywell PEHA