

## Wall mounting socket outlet - straight, housing dimensions 102x102 mm



| Product description           |  |
|-------------------------------|--|
| BALS-Prd.-Nr                  | 110564                                       |
| EAN                           | 4024941938617                                |
| product category (PG)         | TE wall mounting socket outlet Quick-Connect |
| current (A)                   | 16A  |
| number of poles (P99)         | 4p   |
| number of poles (P)           | 3P+PE  |
| position of earth contact (H) | 9 h  |
| voltage (V)                   | 200 up to 250V                               |

| Product description         |  |
|-----------------------------|--|
| frequency (HZ)              | 50 and 60Hz  |
| protection degree (SA)      | IP67   |
| colour code 1 (KF1)         | blue RAL 5015  |
| Colour of appliance         | Hinged lid blue RAL 5015, Enclosure grey RAL 7035  |
| connection design (AT)      | screwless spring terminals as cage clamp with Kontex-contact   |
| maximum conductor size (LQ) | 4,0 qmm  |
| cable entry (KE)            | 3 sides 2x M20/25, 1 side 1x M20/25, to break out  |
| Height                      | 102mm  |
| Width                       | 102mm  |
| Depth                       | 126mm  |
| dimension of enclosure (GG) | 102x102 mm (HxW)   |
| material of enclosure (GM)  | Polyamide  |
| contact                     | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties |                                    |
|---------------------------------|------------------------------------|
|                                 | All cable entries are to break out |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.355 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |

| Logistics data |               |
|----------------|---------------|
| EAN            | 4024941938617 |
| Length         | 126 mm        |
| Width          | 102 mm        |
| Height         | 102 mm        |
| Weight         | 0.356 kg      |
| Volume         | 1,310.904 ccm |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941827492 |
| Length         | 325 mm        |
| Width          | 217 mm        |
| Height         | 210 mm        |
| Weight         | 3.756 kg      |
| Volume         | 13,588.4 ccm  |



1 MB 121

| Ampere Polzahl             | 16<br>3  | 16<br>4  | 16<br>5  | 32<br>3  | 32<br>4  | 32<br>5  |
|----------------------------|----------|----------|----------|----------|----------|----------|
| a                          | 102,0    | 102,0    | 102,0    | 102,0    | 102,0    | 102,0    |
| b                          | 102,0    | 102,0    | 102,0    | 102,0    | 102,0    | 102,0    |
| c                          | 88,0     | 88,0     | 88,0     | 88,0     | 88,0     | 88,0     |
| d                          | 88,0     | 88,0     | 88,0     | 88,0     | 88,0     | 88,0     |
| e                          | 68,0     | 68,0     | 68,0     | 68,0     | 68,0     | 68,0     |
| f                          | 124,0    | 125,0    | 124,0    | 134,0    | 134,0    | 134,0    |
| g                          | 4,0      | 4,0      | 4,0      | 4,0      | 4,0      | 4,0      |
| h ø                        | 4,5      | 4,5      | 4,5      | 4,5      | 4,5      | 4,5      |
| i                          | 2xM20/25 | 2xM20/25 | 2xM20/25 | 2xM20/25 | 2xM20/25 | 2xM20/25 |
| k                          | M20/25   | M20/25   | M20/25   | M20/25   | M20/25   | M20/25   |
| Leiter mm <sup>2</sup> min | 1,5      | 1,5      | 1,5      | 2,5      | 2,5      | 2,5      |
| Leiter mm <sup>2</sup> max | 4        | 4        | 4        | 10       | 10       | 10       |