



Special features

- Suitable for workplaces with screens
- Very low glare value
- 230 V direct connection
- Including power supply

Housing Material	Aluminium	Life Time L70 / B50	50000 h
Housing Color	White	Switching Cycles	100000
Material of Lens	Plastic	Power Consumption	36 kWh/1000h
Protection Class Lamp	Protection class III/safety extra-low voltage	Energy Efficiency Class	D
Protection Class Power Plug	Protection class II/protective insulation		
Rated Input	30.5 W		
Rated Input Voltage	220-240 V/AC		
Power Supply Unit incl.	Yes		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	4000 lm		
Luminous Efficiency	131.1 lm/W		
Rated Angle of Reflection	90 Degree		
UGR	19		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	295 mm		
Width	1195 mm		
Height	32 mm		
Working Temperature	-20 to 45 °C		
Storage Temperature	-40 to 80 °C		
IP Protection Class	IP 40		
IK Protection Class	IK03		