

# D-Sub F AWG 22-26 HMC contact Cat. 7 mod



Part number	09 93 200 5476
Specification	D-Sub F AWG 22-26 HMC contact Cat. 7 mod
HARTING eCatalogue	https://b2b.harting.com/09932005476

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Contacts
Series	D-Sub
Type of contact	Crimp contact

## Version

Gender	Female
Manufacturing process	Turned contacts

# Technical characteristics

Conductor cross-section	0.25 0.52 mm²
Conductor cross-section	AWG 26 AWG 22
Contact resistance	≤10 mΩ
Stripping length	4 mm
Performance level	1 acc. to CECC 75301-802
Mating cycles with other HMC components	≥10,000

# Material properties

Material (contacts)	Copper alloy
Surface (contacts)	HMC gold plated
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption

Page 1 / 2 | Creation date 2022-10-26 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



## Material properties

China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	b51e5b97-eeb5-438b-8538-f1771d43c17d
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead
Commercial data	

# Packaging size100Net weight0.27 gCountry of originGermanyEuropean customs tariff number85366990GTIN5713140229235eCl@ss27440204 Contact for industrial connectors