



Special features

- Light colour adjustable in 3 stages
- Low glare value
- Low housing depth
- Optionally available as pendant lamp

Housing Material	Aluminium	Storage Temperature	-40 to 80 °C
Housing Color	White	IP Protection Class	IP 40
Material of Lens	PMMA	IK Protection Class	IK03
Protection Class	Protection class III/safety extra-low voltage	Life Time L70 / B50	40000 h
Operating Mode	Constant current	Switching Cycles	100000
Rated Input	36 W	Power Consumption	36 kWh/1000h
Rated Input Voltage	33-38 V/DC	Energy Efficiency Class	F
Rated Current	1050 mA		
Power Supply Unit incl.	No		
Dimmable	Yes		
Control technology	Dimmable via optional power supply unit		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000/4000/6000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	3570/3990/3780 lm		
Rated Luminous Flux 2	3990 lm		
Luminous Efficiency	105 lm/W		
Rated Angle of Reflection	120 Degree		
UGR	22		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	1195 mm		
Width	295 mm		
Height	9 mm		
Working Temperature	-20 to 45 °C		