



WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
25	AWG 30	25
26	AWG 30	26

HARTING P/N	LENGTH ( L )
33152430100065	100±3
33152430200065	200±5
33152430500065	500±5

HAR-FLEX 26 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

HAR-FLEX 26 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG, THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE  
HARTING P/N

	All Dimensions in mm Original Size DIN A3		Scale 2:1	Free size tol. \	Ref. \
	All rights reserved Department HCS - CN		Created by LINI Lin	Inspected by QINL Qin	Standardisation QINL Qin
HARTING Customised Solutions D-32339 Espelkamp			Title Har-Flex 26 Pole, Dul-end, With SR, L=xxMM		Date 2019-08-03
			Type TB	Number 33 15 243 XXX0065	State Final Release
					Doc-Key / ECM-Nr. 100834806/UGD/000/A 500000156103
					Rev. A
					Page 1/1