




- Special features**
- Including 1.2 m connecting cable with IP44 shaped plug

|                                              |                                         |                                 |              |
|----------------------------------------------|-----------------------------------------|---------------------------------|--------------|
| <b>Housing Material</b>                      | Die-cast aluminium                      | <b>IP Protection Class Lamp</b> | IP 65        |
| <b>Housing Color</b>                         | Silver                                  | <b>IP Protection Class Plug</b> | IP 44        |
| <b>Material of Lens</b>                      | Glass                                   | <b>IK Protection Class</b>      | IK08         |
| <b>Protection Class</b>                      | Protection class I/protective grounding | <b>Life Time L70 / B50</b>      | 30000 h      |
| <b>Rated Input</b>                           | 15 W                                    | <b>Switching Cycles</b>         | 150000       |
| <b>Rated Input Voltage</b>                   | 220-240 V/AC 50 / 60 Hz                 | <b>Power Consumption</b>        | 15 kWh/1000h |
| <b>Frequency</b>                             |                                         | <b>Energy Efficiency Class</b>  | E            |
| <b>Power Supply Unit incl.</b>               | Yes                                     |                                 |              |
| <b>Connection Cable Primary</b>              | Yes                                     |                                 |              |
| <b>Primary Connection</b>                    | Power plug IP44                         |                                 |              |
| <b>Primary Cable Length</b>                  | 1.2 m                                   |                                 |              |
| <b>Connection Type According to Standard</b> | Typ Y                                   |                                 |              |
| <b>Dimmable</b>                              | No                                      |                                 |              |
| <b>Motion Detector</b>                       | No                                      |                                 |              |
| <b>Light Source</b>                          | LED, Light source not changeable        |                                 |              |
| <b>Color Temperature</b>                     | 4000 K                                  |                                 |              |
| <b>Colour Consistency</b>                    | 5 SDCM                                  |                                 |              |
| <b>Colour Rendering Index (Ra)</b>           | 80                                      |                                 |              |
| <b>Rated Luminous Flux</b>                   | 1950 lm                                 |                                 |              |
| <b>Rated Angle of Reflection</b>             | 100 Degree                              |                                 |              |
| <b>Distribution Characteristic 120°</b>      | DLS                                     |                                 |              |
| <b>Light Exit Surfaces</b>                   | 1                                       |                                 |              |
| <b>Light characteristics</b>                 | Direct                                  |                                 |              |
| <b>Light direction</b>                       | Below                                   |                                 |              |
| <b>Length</b>                                | 179 mm                                  |                                 |              |
| <b>Width</b>                                 | 143.6 mm                                |                                 |              |
| <b>Height</b>                                | 27 mm                                   |                                 |              |
| <b>Working Temperature</b>                   | -20 to 40 °C                            |                                 |              |
| <b>Storage Temperature</b>                   | -10 to 60 °C                            |                                 |              |