



The new COLT series is a genuine all-rounder outdoors: Powerful, freely rotatable and tiltable and equipped with the latest LED technology, the surface-mounted lamps deliver atmospheric illumination concepts in any outdoor application and cut a fine figure even when switched off thanks to their striking design.

#### Special features

- Replaceable reflectors
- Including clear/frosted glass pane
- Including honeycomb filter
- Feed-through wiring possible

<b>Housing Material</b>	Die-cast aluminium	<b>Base height</b>	2.5 mm
<b>Housing Color</b>	Black	<b>Base diameter</b>	65 mm
<b>Material of Lens</b>	Glass	<b>Working Temperature</b>	-30 to 40 °C
<b>Protection Class</b>	Protection class I/protective grounding	<b>Storage Temperature</b>	-40 to 80 °C
<b>Rated Input</b>	4 W	<b>IP Protection Class Lamp</b>	IP 65
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz	<b>IP Protection Class Plug</b>	IP 44
<b>Power Supply Unit incl.</b>	Yes	<b>Life Time L70 / B50</b>	50000 h
<b>Connection Cable Primary</b>	Yes	<b>Switching Cycles</b>	15000
<b>Primary Connection</b>	Power plug IP44	<b>Power Consumption</b>	4 kWh/1000h
<b>Primary Cable Length</b>	2 m	<b>Energy Efficiency Class</b>	G
<b>Connection Type According to Standard</b>	Typ Y		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	240 lm		
<b>Rated Angle of Reflection</b>	36 Degree		
<b>Light Distribution</b>	Symmetric		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Swivel Angle</b>	180 Degree		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Top		
<b>Length</b>	65 mm		
<b>Height</b>	120 mm		
<b>Diameter</b>	50 mm		