

**Special features**

- Can be dimmed using leading-edge/trailing-edge phase dimmers
- Ideal for retrofitting existing installations, since it can be dimmed primarily with rotary/push-button dimmers (C-compatible)
- Cannot be combined with PWM dimmers such as RF, DMX, DALI or KNX
- Flicker-free
- Secured against short circuits and overloads
- Overheating protection

<b>Housing Material</b>	Plastic
<b>Housing Color</b>	Black
<b>Operating Mode</b>	Constant voltage
<b>Protection Class</b>	Protection class II/protective insulation
<b>Power</b>	2.5-25 W
<b>Output Voltage</b>	24 V/DC
<b>Output Current</b>	105-1040 mA
<b>Dimmable</b>	Yes
<b>Control</b>	Leading-edge dimmer, Trailing-edge dimmer
<b>Number of Channels</b>	1
<b>Power Factor</b>	0.95
<b>Connection Type</b>	Clamp
<b>Number of Circuit Breaker B10A max.</b>	35
<b>Number of Circuit Breaker B16A max.</b>	56
<b>Number of Circuit Breaker C10A max.</b>	35
<b>Number of Circuit Breaker C16A max.</b>	56
<b>Inrush Current max.</b>	10 A / 100 µs
<b>Capacitive Load</b>	9520 µF
<b>Reference Point Tc</b>	70 °C
<b>Working Temperature</b>	-20 to 50 °C
<b>Storage Temperature</b>	-20 to 70 °C
<b>IP Protection Class</b>	IP 20
<b>Life Time</b>	30000 h
<b>Length</b>	122 mm
<b>Width</b>	52 mm
<b>Height</b>	30 mm
<b>Product weight</b>	100 g

