



Housing Material	Die-cast aluminium
Housing Color	White
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	9 W
Rated Input Voltage	23-24 V/DC
Rated Current	350 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Dimmable	Yes
Control technology	Dimmable via optional power supply unit
Motion Detector	No

Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 20
Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption	9 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	870 lm
Luminous Efficiency	96.7 lm/W
Rated Angle of Reflection	115 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	20 mm
Diameter	180 mm
Installation Depth	20 mm
Cut Out Diameter	169 mm
Product weight	310 g