



Housing Material	Die-cast aluminium	Light Exit Surfaces	1
Housing Color	Grey	Light characteristics	Direct
Material of Lens	Plastic	Light direction	Below
Protection Class	Protection class III/safety extra-low voltage	Length	175 mm
Operating Mode	Constant voltage	Width	92 mm
Rated Input	2.2 W	Height	330 mm
Rated Input Voltage	3.7 V/DC	Base length	175 mm
Power Supply Unit incl.	No	Base width	103 mm
Connection Type	USB	Base height	15 mm
Dimmable	Yes	Product weight	1450 g
Control technology	Touch-Sensor	Working Temperature	-20 to 45 °C
Motion Detector	No	Storage Temperature	-40 to 60 °C
Accumulator/Battery Operated	Yes	IP Protection Class	IP 54
Rechargeable/battery included	Yes	Life Time L70 / B50	30000 h
Number of Accumulator/Battery	1	Switching Cycles	15000
Type of Accumulator/Battery	Li-Ion battery type 18650		
Accumulator/Battery Capacity	4400 mAh		
Accumulator/Battery Voltage	3.7 V/DC		
Type of Accumulator/Battery 2	Li-Ion battery type 18650		
Accumulator/Battery Capacity 2	2200 mAh		
Accumulator/Battery Voltage 2	3.7 V/DC		
Number of Accumulator/Battery 2	1		
Accumulator Charging Time	5-7 h		
Accumulator Operating Time	10 h		
Light Source	LED, Light source not changeable		
Lightcolor	Warm white (WW)		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	212 lm		
Luminous Efficiency	96.4 lm/W		
Rated Angle of Reflection	50 Degree		