



<b>Housing Material</b>	Die-cast aluminium	<b>Diameter</b>	112 mm
<b>Housing Color</b>	Grey	<b>Product weight</b>	835 g
<b>Housing Surface</b>	Matt	<b>Working Temperature</b>	-20 to 40 °C
<b>Material of Lens</b>	Polycarbonate - PC	<b>Storage Temperature</b>	-20 to 50 °C
<b>Surface Structure of Lens</b>	Clear	<b>IP Protection Class</b>	IP 65
<b>Protection Class</b>	Protection class III/safety extra-low voltage	<b>IK Protection Class</b>	IK04
<b>Rated Input</b>	3.5 W	<b>Life Time L70 / B50</b>	20000 h
<b>Rated Input Voltage</b>	3.7 V/DC	<b>Power Consumption</b>	4 kWh/1000h
<b>Dimmable</b>	Yes		
<b>Control technology</b>	Touch-Sensor		
<b>Motion Detector</b>	No		
<b>Accumulator/Battery Operated</b>	Yes		
<b>Rechargeable/battery included</b>	Yes		
<b>Number of Accumulator/Battery</b>	1		
<b>Type of Accumulator/Battery</b>	Li-Ion battery type 18650		
<b>Accumulator/Battery Capacity</b>	4400 mAh		
<b>Accumulator/Battery Voltage</b>	3.7 V		
<b>Accumulator Charging Time</b>	6.5 h		
<b>Accumulator Operating Time</b>	8 h		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Lightcolor</b>	Warm white (WW)		
<b>Color Temperature</b>	2200/3000 K		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	270 lm		
<b>Luminous Efficiency</b>	77.1 lm/W		
<b>Rated Angle of Reflection</b>	100 Degree		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Height</b>	370 mm		