



<b>Housing Material</b>	Aluminium	<b>IP Protection Class</b>	IP 20
<b>Housing Color</b>	White	<b>Life Time L70 / B50</b>	43800 h
<b>Housing Surface</b>	Matt	<b>Switching Cycles</b>	50000
<b>Material of Lens</b>	Polycarbonate - PC	<b>Power Consumption</b>	28 kWh/1000h
<b>Protection Class</b>	Protection class II/protective insulation	<b>Energy Efficiency Class</b>	E
<b>Rated Input</b>	28 W		
<b>Rated Input Voltage Frequency</b>	200-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Adapter		
<b>Dimmable</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Lightcolor</b>	Warm white (WW)		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	3200 lm		
<b>Luminous Efficiency</b>	114.3 lm/W		
<b>Rated Angle of Reflection</b>	110 Degree		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Length</b>	1087 mm		
<b>Width</b>	62 mm		
<b>Height</b>	32 mm		
<b>Product weight</b>	745 g		
<b>Working Temperature</b>	-25 to 45 °C		
<b>Storage Temperature</b>	-25 to 50 °C		