



C1  
HAR-FLEX 68 POLE FEMALE CONNECTOR  
WITH STRAIN RELIEF

C2  
HAR-FLEX 68 POLE FEMALE CONNECTOR  
WITH STRAIN RELIEF

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
67	AWG 30	67
68	AWG 30	68

HARTING P/N	LENGTH ( L )
33152430100385	100±3
33152430200385	200±5
33152430500385	500±5
33152431450385	1450±10

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG, THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE  
HARTING P/N

	All rights reserved Department HCS - CN HARTING Customised Solutions D-32339 Espelkamp	All Dimensions in mm Original Size DIN A3	Scale 2:1	Free size tol. \	Ref. \
		Created by LINI Lin	Inspected by LIANL Lian	Standardisation LIANL Lian	Date 2022-05-10
Title Har-Flex 68 Pole, Dul-end, With SR, L=XX MM					Doc-Key / ECM-Nr. 100835288/UGD/000/B 500000217515
Type TB				Number 3315243XXX0385	Rev. B
					Page 1/2

